



\* These units are available in 1/2", 9/16", 5/8" and 3/4" bore sizes.

**A part number suffix of:**

- 1 represents 1/2" bore
- 2 represents 9/16" bore
- 3 represents 5/8" bore
- 4 represents 3/4" bore

- These pre-lubricated and sealed roller turn rollers can be used with either plain bolts or bolts with a grease provision.
- Inner grease shelves keep the lubricant at each ball race providing improved reliability.
- These units are lubricated with SHOP STD. grease which has an operating range of -40° to 350°F.
- Special grease available upon request.

| CATALOG NUMBER | OUTSIDE DIAMETER | LENGTH THRU BORE | FACE LENGTH | * INSIDE DIAMETER | LUBE STYLE | APPROX. WEIGHT (LBS) |
|----------------|------------------|------------------|-------------|-------------------|------------|----------------------|
| 45373-1        | 2-5/16"          | 1-5/8"           | 1-1/2"      | 1/2"              | Re-lube    | 1.7                  |
| 44218-1        | 2-9/16"          | 3-7/8"           | 3-1/2"      | 1/2"              | Re-lube    | 4.3                  |
| 44045-1Z       | 2-9/16"          | 4-1/4"           | 3-7/8"      | 1/2"              | S.F.L.     | 3.4                  |
| 44120-1        | 2-5/8"           | 4-1/4"           | 3-7/8"      | 1/2"              | Re-lube    | 5.0                  |
| 3323-1         | 2-3/4"           | 1-7/8"           | 1-11/16"    | 1/2"              | Re-lube    | 2.1                  |
| 33615-1        | 2-3/4"           | 2"               | 1-13/16"    | 1/2"              | Re-lube    | 2.2                  |
| 8793-1         | 2-3/4"           | 2-1/8"           | 1-15/16"    | 1/2"              | Re-lube    | 2.3                  |
| 3131-1         | 2-3/4"           | 2-9/16"          | 2-3/8"      | 1/2"              | Re-lube    | 2.7                  |
| 3112-1         | 2-3/4"           | 2-3/4"           | 2-9/16"     | 1/2"              | Re-lube    | 2.9                  |
| 44810-1Z       | 2-3/4"           | 2-3/4"           | 2-9/16"     | 1/2"              | -          | 2.9                  |
| 3132-1         | 2-3/4"           | 3"               | 2-13/16"    | 1/2"              | Re-lube    | 3.1                  |
| 3134-1         | 2-3/4"           | 3-1/2"           | 3-5/16"     | 1/2"              | Re-lube    | 3.5                  |
| 44607-1        | 2-3/4"           | 4-1/4"           | 4-1/16"     | 1/2"              | Re-lube    | 4.2                  |
| 44622-1        | 3"               | 2-1/8"           | 1-15/16"    | 1/2"              | Re-lube    | 3.0                  |
| 42535-1        | 3"               | 2-3/4"           | 2-9/16"     | 1/2"              | Re-lube    | 3.7                  |
| 43663-1        | 3-1/4"           | 3"               | 2-3/4"      | 1/2"              | Re-lube    | 6.1                  |
| 44045-1Z       | 3-1/2"           | 4-1/4"           | 3-7/8"      | 1/2"              | -          | 4.7                  |

CIGNYS may make dimensional changes without notice to improve its product or the application. On request, CIGNYS engineers will furnish certified data as required.